

SW946 Silicone Spray

- **DESCRIPTION:** Silicone Spray is colorless, non-staining, waxless and heat stable; unaffected by temperatures ranging from -40°C (-40°F) to over 200°C (392°F). This friction reducer results in speedier clean-up of parts and equipment and increased production through cleaner job processing. It remains dry and is non-staining. No. 946 complies with FDA regulations applicable to the food packaging/ food processing industry.
- **USE ON:** Lubricant and release agent for use on: Ovens, freezers, conveyors, belts and chutes. May be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures and as a lubricant for machine parts and equipment in locations with incidental exposure of the lubricated part to food. **FOR USE IN THE MANUFACTURING PROCESS ONLY.**

SPECS:	Can Size:	20 oz.	
	Net Weight:	11 oz.	
	Shipping Weight:	12 lbs.	
	Packaged:	12 cans per case	
	SAP Number:	1000007771	
	UPC Number:	0 41911 00946 1	ayway
PHYSICAL	Color:	Colorless	NO. 946
CHARACTERISTICS:	Fragrance:	Solvent	
REGULATORY:	Shelf Life:	5 Tedis	ICONE
	Recyclable Packaging:	Yes	PRAY 📕
	VOC Compliant CARB/OTC:	Yes	
	CPSC Flammability:	Required to be labeled as extremely flammable	
	NSF Certified:		
	24 HR. MEDICAL EMERGENCY:	1-866-836-8855	NSF
FEATURES:	• HEAT-STABLE SILICONE RELE • COLORLESS, NON-STAINING		nted Compounds ogam Listed HT Reg #13401 TRIAL USE ONLY
See back panel for First Aid and additional Precautionary Statements. KEEP OUT OF REACH OF CHILDREN. CONSULT SDS BEFORE USING MADE IN THE UNTH GLOBALLY SOURCED MATERIALS			

Manufactured by: **SPRAYWAY, INC.** 2651 Warrenville Rd. Ste 300 | Downers Grove, IL 60515 800-332-9000 • Fax: 630-543-7797 • www.spraywayinc.com

REORDER/ITEM NUMBER SW-946